

SUPER-DRY

FC/FD Series | Mini Filters and Desiccant Dryers |

Protect your compressed air application



- High efficiency
- Portable and lightweight
- Continuous clean dry air



Specifications and Engineering Data

The Super-Dry FC/FD contains:

- A coalescer filter (FC) designed to filter water, oil and other contaminants
- A miniature desiccant dryer (FD) to remove moisture from your compressed air system

Quick change replacement kit



FC / FD Series elements



FD element



FC element

Specifications and ordering information:

Model	Air Flow @ 100 psig scfm	Inlet/Outlet NPT in	Dimensions			Weight lbs	Replacement Kit
			A	B	C		
FC-½	20	½	3 ⅛	7 ½	6 ½	1.2	EFC-½
FC-1	40	1	3 ⅝	11 ⅞	10	3.8	EFC-1
FD-½	20	½	3 ⅛	7 ½	6 ½	1.2	EFD-½
FD-1	40	1	3 ⅝	11 ⅞	10	3.8	EFD-1

FC-½ & FD-½: Maximum inlet temperature: 100 °F (38°C) Maximum inlet pressure: 130 psig Plastic Bowl

FC-1 & FD-1: Maximum inlet temperature: 100 °F (38°C) Maximum inlet pressure: 150 psig Metal Bowl

